

Accessory - Apron

Technical Data Sheet

Product Code DD603


Description Disposable apron with neck loop and ties waist

Material
 Fabric: High performance external barrier film coated to non-woven fabric
 Elastic: Neoprene Rubber (latex free)

Color Yellow

Spec

| Item | Description | Length |
|------|--------------|---------|
| A | Body Length | 115 cm |
| B | Neck Width | 23 cm |
| C | Bottom Width | 75 cm |
| D | Belt Width | 0.5 cm |
| E | Neck Loop | 58.5 cm |
| F | Belt Length | 66.5 cm |



CE Approval


| | |
|-------------------------|---|
| EN 13034:2005 + A1:2009 | Type PB [4], limited life, partial body protection against liquid chemicals |
| EN 14126:2003 | Type PB [4-B], limited life, partial body protection against infective agents |

Properties

| FABRIC PHYSICAL PROPERTIES | TEST METHOD | RESULT | CLASS | FABRIC PHYSICAL PROPERTIES | TEST METHOD | RESULT | |
|----------------------------|-------------|-------------|---------|-----------------------------------|--------------------|-----------------------|---------|
| Abrasion Resistance | EN 530 | >100 cycles | Class 2 | Azo Dyes | EN 14362-1 | Pass | |
| Flex Cracking Resistance | ISO 7854 | >1K cycles | Class 1 | pH Value | ISO 3071 | Pass | |
| Trapezoidal Tear Resist. | MD | >40N | Class 3 | FABRIC CHEMICAL PROPERTIES | PENETRATION | REPELLENCY | |
| | CD | >40N | | | | | |
| Tensile Strength | MD | >100N | Class 2 | Sulphuric acid 30% | Class 3 | Class 3 | |
| | CD | >60N | | Sodium Hydroxide 10% | Class 3 | Class 3 | |
| Puncture Resistance | EN 863 | >5N | Class 1 | o-Xylene | Class 3 | Class 2 | |
| Seam Strength | ISO 13935-2 | >75N | Class 3 | Butan-1-ol | Class 3 | Class 2 | |
| CHEMICAL PERMEATION* | | TEST METHOD | | FABRIC PERFORMANCE | | SEAM TAPE PERFORMANCE | |
| 10% Formaldehyde | | EN 374-3 | | >480 min | Class 6 | >480 min | Class 6 |
| Methanol | | EN 374-3 | | >480 min | Class 6 | 13 min | Class 1 |
| 98% Sulphuric acid | | EN 374-3 | | >480 min | Class 6 | >480 min | Class 6 |

Note*: Please contact your local distributor for the full list of tested chemicals and the results of resistance against various chemicals

Seam Type



Stitched with Tape Seam

Stitch seam with chemical barrier tape for a higher protection level to particulate and liquid splashes

Packing 100 pcs per box

Storage and Disposal

- Store in dry, clean conditions in original packaging.
- Store away from direct sunlight, sources of high temperature, and solvent vapors.
- Store within the temperature range -20°C to +25°C (-4°F to +68°F) and with relative humidity below 80%.
- Shelf life is 60 months from date of manufacture when stored as stated above.
- Replace garments if damaged, heavily contaminated or in accordance with local work practice.
- Handle and dispose of contaminated garments with care and in accordance with national regulations.

~~☒~~ Do not wash

~~☒~~ Do not clean dry

~~☒~~ Flammable

~~☒~~ Do not iron

~~☒~~ Do not tumble dry