

Accessory - Sleeve Cover

Technical Data Sheet

Product Code DD602


Description Disposable sleeve cover with elasticated opening in each end

Material Fabric: High performance external barrier film coated to non-woven fabric
Elastic: Neoprene Rubber (latex free)

Color Yellow

Spec

Item	Description	Length
A	Wrist Relax	9 cm
	Wrist Stretch	19 cm
B	Length	47 cm
C	Width	19 cm



CE Approval	EN 13034:2005 + A1:2009	Type PB [4], limited life, partial body protection against liquid chemicals
	EN 14126:2003	Type PB [4-B], limited life, partial body protection against infective agents

Properties

FABRIC PHYSICAL PROPERTIES	TEST METHOD	RESULT	CLASS	FABRIC PHYSICAL PROPERTIES	TEST METHOD	RESULT
Abrasion Resistance	EN 530	>100 cycles	Class 2	Azo Dyes	EN 14362-1	Pass
Flex Cracking Resistance	ISO 7854	>1K cycles	Class 1	pH Value	ISO 3071	Pass
Trapezoidal Tear Resist.	MD	ISO 9073-4	Class 3	FABRIC CHEMICAL PROPERTIES		
	CD			>40N	PENETRATION	REPELLENCY
Tensile Strength	MD	ISO 13934-1	Class 2	Sulphuric acid 30%	Class 3	Class 3
	CD			>60N	Sodium Hydroxide 10%	Class 3
Puncture Resistance	EN 863	>5N	Class 1	o-Xylene	Class 3	Class 2
Seam Strength	ISO 13935-2	>75N	Class 3	Butan-1-ol	Class 3	Class 2
CHEMICAL PERMEATION*		TEST METHOD	FABRIC PERFORMANCE		SEAM TAPE PERFORMANCE	
10% Formaldehyde		EN 374-3	>480 min	Class 6	>480 min	Class 6
Methanol		EN 374-3	>480 min	Class 6	13 min	Class 1
98% Sulphuric acid		EN 374-3	>480 min	Class 6	>480 min	Class 6

Note*: Please contact your local distributor for the full list of tested chemicals and the results of resistance against various chemicals

Seam Type



Stitched with Tape Seam

Stitch seam with chemical barrier tape for a higher protection level to particulate and liquid splashes

Packing 100 pairs per box

Storage and Disposal

- Store in dry, clean conditions in original packaging.
- Store away from direct sunlight, sources of high temperature, and solvent vapors.
- Store within the temperature range -20°C to +25°C (-4°F to +68°F) and with relative humidity below 80%.
- Shelf life is 60 months from date of manufacture when stored as stated above.
- Replace garments if damaged, heavily contaminated or in accordance with local work practice.
- Handle and dispose of contaminated garments with care and in accordance with national regulations.

~~☒~~ Do not wash

~~☒~~ Do not clean dry

Flammable

~~☒~~ Do not iron

~~☒~~ Do not tumble dry