

Dust & Liquid Splash Resistant Coverall

- **Lightweight and cost-effective**

The light microporous fabric offers comfort and protection against hazardous liquid splash and particulate.

- **Exceeds EN 368 & EN 14126**

The performance levels exceed the WHO protective clothing specification option 1 for Ebola infection control.

- **Good breathability**

High water-vapour transmission & soft texture ensures wearer comfort.

- **Low linting**

Reducing the risk of contamination to work environment.

3-piece hood



Zipper fastens to underside of chin



Fully elasticated waist



Ample crotch



PERFORMANCE OF ULTITEC 1800



WHOLE SUIT TEST PERFORMANCE		RESULT
Type 5 Inward Leakage Test	EN 13982-1:2004 + A1:2010	Pass
Type 6 Low Level Spray Test	EN13034:2005 + A1:2009	Pass
Against Radioactive Contamination	EN1073-2: 2002	Class 1


FABRIC PHYSICAL PROPERTIES	TEST METHOD	CLASS		
Classifications in accordance with EN 14325:2004				
Abrasion Resistance	EN 530	1		
Flex Cracking Resistance	ISO 7854 B	3		
Trapezoidal Tear Resist.	ISO 9073-4	2		
Tensile Strength	ISO 13934-1	1		
Puncture Resistance	EN 863	1		
Seam Strength	ISO 13935-2	5		
Antistaticity	EN1149 - 5	Pass		
pH Value	ISO 3071	Pass		
Resistance to Ignition	EN 13274-4	Pass		
Against Infective Agents	EN 14126	Pass		
ISO 16603	ISO 16604	ISO 22610	ISO 22611	ISO 22612
6	1	6	3	3
Resistance to Chemical Penetration ISO 6530				
		PENETRATION	REPELLENCY	
Sulphuric acid 30%		3	3	
Sodium Hydroxide 10%		3	3	

APPLICATION

Agriculture, Automotive, Biological Hazards, Construction, Chemical Plants, Food Industry, Petrochemical, Painting

FABRIC & SEAM

4-thread overlapped seam



- 7-9 stitched per inch
- Heavier thread fibre is above 150D
- Bite depth 4 mm

Microporous film fabric

Waterproof & breathable !!

