

# Accessory - Boot Cover

## Technical Data Sheet

**Product Code** DD605


**Description** Disposable boot cover with elasticated opening

**Material** Fabric: High performance external barrier film coated to non-woven fabric  
Elastic: Neoprene Rubber (latex free)

**Color** Yellow

**Spec**

Item	Description	Length
A	Cuff Relax	13 cm
	Cuff Stretch	24 cm
B	Ankle to Cuff	26 cm
C	Height to Ankle	16 cm
D	Length	38 cm




<b>CE Approval</b>	EN 13034:2005 + A1:2009	Type PB [4], limited life, partial body protection against liquid chemicals
	EN 14126:2003	Type PB [4-B], limited life, partial body protection against infective agents

### Properties

FABRIC PHYSICAL PROPERTIES	TEST METHOD	RESULT	CLASS	FABRIC PHYSICAL PROPERTIES	TEST METHOD	RESULT
Abrasion Resistance	EN 530	>100 cycles	Class 2	Azo Dyes	EN 14362-1	Pass
Flex Cracking Resistance	ISO 7854	>1K cycles	Class 1	pH Value	ISO 3071	Pass
Trapezoidal Tear Resist.	MD	>40N	Class 3	<b>FABRIC CHEMICAL PROPERTIES</b>		
	CD	>40N		<b>PENETRATION</b>	<b>REPELLENCY</b>	
Tensile Strength	MD	>100N	Class 2	Sulphuric acid 30%	Class 3	Class 3
	CD	>60N		Sodium Hydroxide 10%	Class 3	Class 3
Puncture Resistance	EN 863	>5N	Class 1	o-Xylene	Class 3	Class 2
Seam Strength	ISO 13935-2	>75N	Class 3	Butan-1-ol	Class 3	Class 2
<b>CHEMICAL PERMEATION*</b>		<b>TEST METHOD</b>	<b>FABRIC PERFORMANCE</b>		<b>SEAM TAPE PERFORMANCE</b>	
10% Formaldehyde		EN 374-3	>480 min	Class 6	>480 min	Class 6
Methanol		EN 374-3	>480 min	Class 6	13 min	Class 1
98% Sulphuric acid		EN 374-3	>480 min	Class 6	>480 min	Class 6

Note\*: Please contact your local distributor for the full list of tested chemicals and the results of resistance against various chemicals

### Seam Type



#### Stitched with Tape Seam

Stitch seam with chemical barrier tape for a higher protection level to particulate and liquid splashes

**Packing** 100 pairs per box

### Storage and Disposal

- Store in dry, clean conditions in original packaging.
- Store away from direct sunlight, sources of high temperature, and solvent vapors.
- Store within the temperature range -20°C to +25°C (-4°F to +68°F) and with relative humidity below 80%.
- Shelf life is 60 months from date of manufacture when stored as stated above.
- Replace garments if damaged, heavily contaminated or in accordance with local work practice.
- Handle and dispose of contaminated garments with care and in accordance with national regulations.

Do not wash

Do not clean dry

Flammable

Do not iron

Do not tumble dry