

Oil, Chemical & Infective Agents Resistant Coverall

- The premium microporous fabric offers an outstanding barrier against wide range of chemical liquids, blood, body-fluid and infective agents.
- Breathable & comfortable

Fabric allows water-vapour transmission, which offers breathability to keep the wearer comfortable.

Protective suits against pesticides
 Meets DIN 32781 requirement on both protection and comfort in agriculture application.

Low linting

Reducing the risk of contamination to work environment.

- Suitable for ISO class 6 and above cleanroom
- Sealed seam

PERFORMANCE OF ULTITEC 3000T





Isopropanol











WHOLE SUIT TEST PERFORMANCE		RESULT	
Type 5	EN 13982-1:2004 +	Pass	
Inward Leakage Test	A1:2010	rdSS	
Туре 6	EN13034:2005 +	Pass	
Low Level Spray Test	A1:2009	Pd55	
Against Radioactive Contamination	EN1073-2: 2002	Class 1	
Against Pesticides	DIN 32781	Pass	

FABRIC PHYSICAL PROPER	RTIES TE	ST METHOD	CLASS	
Classifications in accordance with EN 14325:2004				
Abrasion Resistance	EN	N 530	2	
Flex Cracking Resistance	IS	O 7854 B	5	
Trapezoidal Tear Resist.	IS	O 9073-4	1	
Tensile Strength	IS	0 13934-1	1	
Puncture Resistance	EN	N 863	1	
Seam Strength	IS	0 13935-2	3	
Burst Resistance	IS	0 13938-1	3	
Antistaticity	EN	N1149 - 5	Pass	
pH Value	IS	0 3071	Pass	
Resistance to Ignition	EN	N 13274-4	Pass	
Resistance to Water Pene	tration EN	N 20811	> 2500 mm	
Water Vapour Resistance	[Ret] IS	0 11092	31.7 m2*Pa/W	
Against Infective Agents	EN	N 14126	Pass	
ISO 16603 ISO 16604	ISO 22610	ISO 22611	ISO 22612	
6 2	6	3	3	
Resistance to Chemical Penetration EN 368				
	PENETRATION		REPELLENCY	
Sulphuric acid 30%		3	3	
Sodium Hydroxide 10% 3		3	3	



APPLICATION

Agriculture, Automotive, Biological Hazards, Chemical Plants, Disaster Management, Pharmaceutical (cleanroom), Petrochemical, Painting

FABRIC & SEAM

4-thread overlocked seam with liquid-proof



- 7-9 stitched per inch
- Heavier thread fibre is above 150D
- Bite depth 4 mm



