



- Product :** ULTITEC 1000L-NA
Dust and Liquid Spray Protective Clothing
NA: None-Antistatic
- Style NO :** DD110 Standard hooded coverall
DD120 Hooded coverall with integral boots
DD130 Collared coverall
DD140 Hooded coverall with knitted cuff
- Material :** Fabric: Multilayer SMS fabric
Zipper: Nylon on polyester braid
Elastic: Neoprene rubber (latex free)
Thread: Polyester
- Color :** White, Blue, Yellow, Red
- Sizing :** An appropriate size should be selected to allow sufficient movement for the task

SIZE	CHEST (CMS)	HEIGHT (CMS)
S	84 - 92	162 - 170
M	92 - 100	170 - 176
L	100 - 108	176 - 182
XL	108 - 116	182 - 188
2XL	116 - 124	188 - 194
3XL	124 - 132	194 - 200
4XL	132 - 140	200 - 206

Protection Level :



Type 5



Type 6



EN 1073-2

⚠ indicate EN 1073-2 excluding clause 4.2 puncture resistance.

Approvals :

CE approved under PPE regulation EU 2016/425, Category III
Module B Certification: SGS Fimko Oy, LTD. Notified Body Number: 0598
Module D Supervision: SGS Fimko Oy, LTD. Notified Body Number: 0598

Design Features :

Zipper fastens to underside of chin; 3-piece hood; Elasticated wrists
Fully elasticated waist; Ample crotch; Elasticated ankles

Storage and Disposal :

- Store in dry, clean conditions in original packaging within the temperature range 15°C to 25°C. (58°F to 78°F) and with relative humidity below 80%.
- Store away from direct sunlight, sources of high temperature, and solvent vapors.
- Shelf life is 60 months from date of manufacture when stored as stated above.
- Handle and dispose of contaminated garments with care and in accordance with national regulations.

Limitations :

Do not wash

Do not dry clean

Do not iron

Do not machine dry

Do not reuse

Keep away from fire

Applications :

Asbestos, Construction, Grinding, Mining Process, Sand Blasting, Waste Cleaning

Technical Data :

The table below shows the performance tested under laboratory conditions. Please note that tests may not reflect the reality of use and do not account for factors such as excessive heat and mechanical wear.

Fabric Physical Properties		Test Method	Result	Class
Abrasion Resistance		EN 530	>10 cycles	Class 1
Flex Cracking Resistance		EN ISO 7854/B	>15,000cycles	Class 4
Trapezoidal Tear Resistance	MD	EN ISO 9073-4	>40 N	Class 3
	CD		>40 N	
Tensile Strength	MD	EN ISO 13934-1	>100 N	Class 2
	CD		>60 N	
Puncture Resistance		EN 863	>5 N	Class 1
Seam Strength		EN ISO 13935-2	>50 N	Class 2
pH Value		EN ISO 3071	Pass	
Azo Colorants		EN 14362-1	Pass	
Color Fastness to Perspiration		EN ISO 105-E04	Pass	
Resistance to Ignition		EN 13274-4	Pass	
Fabric Chemical Properties		Test Method	Penetration	Repellency
Sulfuric Acid 30%		EN ISO 6530	Class 3	Class 3
Sodium Hydroxide 10%		EN ISO 6530	Class 3	Class 3
Whole Suit Test Performance			Result	
Type 5	EN ISO 13982-1:2004+A1:2010	Inward Leakage Test Test method: EN ISO 13982-2:2004	Pass	
Type 6	EN 13034:2005+A1:2009	Low Level Spray Test Test method: EN ISO 17491-4:2008 Method:A	Pass	
EN 1073-2	Protective Clothing Against Radioactive Contamination		Class 1	

Packing :

- 1 piece per PE bag
- 50 pieces per carton