Technique Data Sheet





Product: ULTITEC 500

Light Protection Protective Clothing

Style NO: DD010 Standard Hooded Coverall

DD030 Collared Coverall

Material: Fabric: PPSB fabric

Zipper: Nylon on Polyester Braid Elastic: Neoprene Rubber (latex free)

Thread: Polyester

Color: White, Blue

Sizing: An appropriate size should be selected

to allow sufficient movement for the task

SIZE	CHEST (CMS)	HEIGHT (CMS)
S	84 - 92	162 - 170
M	92 - 100	170 - 176
L	100 - 108	176 - 182
XL	108 - 116	182 - 188
2XL	116 - 124	188 - 194
3XL	124 - 132	194 - 200
4XL	132 - 140	200 - 206

Applications:

Civil Protection, Decorative Work, Construction, Food Processing & Packing

Approvals :

CE approved under PPE regulation EU 2016/425, Category I Module D Supervision: SGS Fimko Oy, LTD. Notified Body Number: 0598

Design Features :

Zipper fastens to underside of chin; 3-piece hood; Elasticated wrists Fully elasticated waist; Ample crotch; Elasticated ankles

Storage and Disposal :

- Store in dry, clean conditions in original packaging within the temperature range 15°C to 25°C. (58°F to 78°F) and with relative humidity below 80%.
- Store away from direct sunlight, sources of high temperature, and solvent vapors.
- Shelf life is 60 months from date of manufacture when stored as stated above.
- Handle and dispose of contaminated garments with care and in accordance with national regulations.

Limitations:

Do not wash

Do not dry clean

Do not iron

Do not machine dry

② D

Do not reuse

K

Keep away from fire

Packing:

- 1 piece per PE bag
- 50 pieces per carton